

No: RAVAPROOF BASE 460P60.20.02.2022

1-Unique identification of the product-type

RAVAPROOF

2-Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)

RAVAPROOF BASE 460P60 Lot number: 022202200301

3-Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

- **EN 13969 Flexible sheets for waterproofing- Bitumen damp proof sheets including bitumen basement tanking sheets**
- **EN 13707 Reinforced bitumen sheets for roof waterproofing**

4-Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Center: RAVAGO GROUP Moerenstraat 85A B-2370 Arendonk BELGIUM
Manufacturer: RBS RAVAGO İNŞAAT YALITIM ÜRÜNLERİ A.Ş. Arslanbey O.S.B. 5th Street No: 7 Kocaeli

5-Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)

...

6-System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+,3

7- In case of the declaration of performance concerning a construction product covered by a harmonised Standard:

Notified body N° 2765, Szutest Ltd. issued certificate of conformity of the factory production control as a result of evaluation and verification of the constancy of performance under system 2+ .

8- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9- Declared Performance

| Essential characteristics | Performance | | | Harmonised Technical Specification |
|--------------------------------------|-------------|-----------|--------------------------|------------------------------------|
| | Unit | Tolerance | RAVAPROOF BASE 460P60 | |
| Tensile strength (MD/CD) | N/50mm | ±100 | 600/450 | EN 13707+13969 |
| Impact resistance | mm | min | NPD | |
| Shear resistance of joints | N/50mm | | NPD | |
| Resistance to static loading Mt.B | Kg | | NPD | |
| Resistance to root penetration | | | NPD | |
| Tearing resistance (with nail(MD/CD) | N | ±30% | 150/160 | |
| External Fire Performance | | | Froof | |
| Reaction to Fire | | | F | |
| Flexibility at low temperature | °C | ≤ | -5 | |
| Artificial ageing +Cold flexibility | °C | | NPD | |
| Artificial ageing +Flow resistance | °C | | NPD | |
| Watertightness -Type T | 60kPa | | Pass | |
| Dangerous Substance | | | none | |

NPD: No Performance Determined

10-The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Kadir Kalkan
R&D Specialist
KOCAELİ, 15.08.2022